

Codan 1232 Air / Water Hose



Codan 1232 - ISO 1403: 2019 type 2

Red, industrial-quality water hose for use in all types of industrial flushing, cleaning, etc. Hard-wearing surface that also has excellent weather and ozone resistance.

From 32 mm: wrapped hose supplied in 40 m lengths. (old type 1210) Working temp. -30°C to +80°C. BP 3x safety factor.

Please contact Codan for further information.

Type nr. 1232

Application: Air / Water Hose

Standard Length: 50 metres

Working Temperature: -30°C to 100°C

Inside: EPDM

Colour: Black

Reinforcement: Polyester

Outside: EPDM

Colour: Red

Standards: ISO 1403: 2019 type 2

Std. branding: -

Inside dia. (mm)	Outside dia. (mm)	Working Pressure BAR	Burst Pressure BAR	Bend Radius (mm)	Weight (g/m)	Product code
12,7	20,7	10	30	0	250	1232013000
15,9	23,9	10	30	0	300	1232016000
19,1	28,5	10	30	0	500	1232019000
25,4	34,8	10	30	0	580	1232025000
32,0	42,4	10	30	0	880	1232032000
38,0	48,4	10	30	0	1.020	1232038000
45,0	55,4	10	30	0	1.200	1232045000
50,0	61,0	10	30	0	1.360	1232051000
63,0	76,2	10	30	0	2.100	1232063000
70,0	83,2	10	30	0	2.360	1232070000
76,0	90,4	10	30	0	2.740	1232076000
102,0	116,8	10	30	0	3.690	1232102000
127,0	143,0	10	30	0	4.950	1232127000
152,0	168,0	10	30	0	5.870	1232152000
203,0	225,0	10	30	0	7.120	1232203000

This hose specification sheet has been prepared with great care in order to provide you with all the information you need. Written advice must be obtained from Codan Rubber before using any hose with untested media or before using in applications not covered in the product data sheet. Codan Rubber recommends regular maintenance, care and inspection of hoses before use. Hoses should be replaced if any physical damage is seen, especially to the cover of the hose or in the area around the couplings. All products must be stored in accordance with ISO 2230:2002 (Storage

of vulcanised Rubber Products). The individual conditions of an application will affect the life time of each product. Therefore please ensure that resistance to chemicals and cleaning procedures in our written product information is complied with. Codan Rubber's warranty is void in the event of misuse such as excessive bending, crushing, stretching, use with incorrect media or use in environments outside the hose specification.

Please contact Codan Rubber for individual product manufacturing tolerances.



Codan Rubber A/S Værkstedvej 45-49, DK-4600 Køge, Denmark Tel. +45 56 64 64 64 Mail: info@codan.com
www.codan.com